

OLYMPUS[®]

Your Vision, Our Future

EVIS EXERA III

EVIS EXERA III GASTROINTESTINAL VIDEOSCOPE

GIF-XP190N

Ultra-slim design with electrosurgery compatibility and outstanding image quality






Main Features

Ultra-slim Design

The 5.4 mm outer diameter of the distal end eases insertion. The shape of the scope tip is carefully formed for smooth removal, which further reduces patient discomfort.

Advanced Image Clarity

This scope delivers superior image quality, compared to conventional models. Its two light guides help to achieve ample brightness for precise diagnosis. The two guides also reduce shadows during the use of endotherapy devices.



White Light



NBI

Advanced Suction Capability

The increase in channel size to 2.2 mm increases suction volume compared to conventional scopes with a 2.0 mm channel.

Wide Viewing Angle

The viewing angle of this ultra-slim scope has been increased to 140 degrees, matching the wide field of vision of larger gastroscopes even in restricted spaces.

Waterproof One-touch Connector

A new connector design minimizes the effort required for setup prior to and in between cases. In addition, it is fully submersible and eliminates the need for a water-resistant cap and the associated risk of an expensive repair due to accidental immersion.



Specifications

Optical System	Field of view	140°
	Direction of view	Forward viewing
	Depth of field	3-100 mm
Insertion Section	Distal end outer diameter	5.4 mm
	Distal end enlarged	
	Insertion tube outer diameter	5.8 mm
	Working length	1100 mm

Instrument Channel	Channel inner diameter	2.2 mm
	Minimum visible distance	3.0 mm from the distal end
Bending Section	Direction from which endotherapy accessories enter and exit the endoscopic image	
		Up 210°
		Down 90°
		Right 100°
Total Length	1420 mm	
	Compatible EVIS EXERA System	Video System Center OLYMPUS CV-190 Xenon Light Source OLYMPUS CLV-190

Image courtesy of Jean-Francois Rey, MD

Specifications, design and accessories are subject to change without any notice or obligation on the part of the manufacturer.